

PARACHUTE OPEN LIFT BAGS

Open End Parachute design with a single point attachment to the load bearing strap arrangement for safe subsea lifting.



Model Name	Part Number	Capacity	Overall Height(M)	Overall Diameter (M)
M25	710144	55 LB	0.75	0.40
M1	710140	110 LB	0.85	0.50
M2	710143	220 LB	1.13	0.60
M5	710168	550 LB	1.92	0.80
M10	710139	1100 LB	2.12	1.00
PR1	710148	2200 LB	2.38	1.30
PR1V	710178	3300 LB	2.86	1.30
PR2	710176	4400 LB	3.02	1.40
PR3	710181	6610 LB	3.95	1.50
PR4	711534	8820 LB	4.00	1.75
PR5	710182	11000 LB	4.25	2.20
PR6	711535	13220 LB	4.25	2.43
PR10	710150	22050 LB	4.85	2.76
PR15	710156	33070 LB	5.10	3.35
PR20	710152	44000 LB	5.60	3.67
PR25	711537	55110 LB	6.20	3.80
PR30	711538	66140 LB	6.10	4.00
PR35	710164	77150 LB	7.00	4.16
PR50	711317	110230 LB	7.30	5.00

Application:

- Safe and controlled subsea lifting operations.
- Ideal for use where a single-point attachment is required.

Key Features:

- Open-end parachute design allows for rapid, controlled ascent and release of buoyancy in underwater operations.
- Simplified rigging ensures secure connection to the load-bearing strap configuration.
- Safety inverter line automatically triggers deflation in the event of a dropped load, preventing uncontrolled ascent.
- Supplied fully assembled with a user manual and service record book for immediate use.

You can rent me!
Visit: jwarentals.com